



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

IMPORTANT: TENDERERS SHOULD READ THE TENDER PAPERS CAREFULLY; SUBMISSION OF TENDER SHALL MEAN THAT THE TENDERER HAS READ AND UNDERSTOOD ALL THE TERMS AND CONDITIONS OF THE TENDER AND AGREES AND BINDS HIMSELF/THEMSELVES TO THE SAME. ALL PAGES OF THE TENDER DOCUMENTS SHOULD BE SIGNED BY THE TENDERER(S) AND RETURNED WITH THE TENDER.

TENDER NO: CTR/LDH/1810/Mach/2017-119

DUE ON : 04.10.2017

DATED: 20.09.2017

AT: 02:00 p.m.

PART – I

INVITATION OF TENDER

From: The General Manager.
Central Tool Room
A-5, Focal Point
Ludhiana-141 010
India.

To :

- 1.0 Sealed Tender for “**Hydraulic Training Kit**” as per specifications given in the attached Schedule (Part-III) are invited by the General Manager, Central Tool Room, Ludhiana, India (hereinafter called the “Tool Room and/or the Purchaser”). The tenders shall be received up to 02.00 p.m. on 04.10.2017 and shall be opened in the presence of intending tenderers at 3:00 p.m. on the next day i.e. 05.10.2017. Tenders received late will not be accepted. Tenders should be accompanied by interest free Earnest Money of an amount of Rs. 40,000/- (Rupees forty thousand only) in the form of Demand Draft / Bank Guarantee in favour of “Central Tool Room Ludhiana” payable at Ludhiana. Tenders without Earnest Money or bank guarantee in lieu thereof will not be accepted. Tenderers registered with DGS&D/GeM and/or NSIC for machine/equipment/goods mentioned in Part-III are exempted from depositing Earnest Money and Security Deposit on submission of proof of registration, alongwith the tender.

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सूक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

- 2.0 Tenders must be submitted only on on-line on www.eprocure.gov.in portal before the stipulated date and time.
- 3.0 a) The tenders should be submitted in two parts. Part 'A' should contain the technical specifications of the kit, which should be described in sufficient details. Detailed technical literature should be enclosed. It should also be accompanied by a list of organizations where similar kits have been supplied by the tenders in India. No price should be indicated in this Part 'A'. DD FOR EARNEST MONEY SHOULD ALSO BE ENCLOSED IN THE SAME ENVELOP, AT THE TIME OF SUBMISSION. All pages of this tender document are to be signed and submitted with this part 'A'.
This envelop should be marked as follows-
- PART 'A'*
Tender for : Hydraulic Training Kit
Tender No. : CTR/LDH/1810/Mach/2017-119
Due on : 04.10.2017
Dated : 20.09.2017
At : 02:00 p.m.
- b) Part 'B' of the tender should contain the prices quoted by the Tenderer for the Kit. It is very important that the prices are quoted with reference to the description of the kit offered in Part 'A' of the tender.
This envelop should be marked as follows-
- PART 'B'*
Tender for : Hydraulic Training Kit
Tender No. : CTR/LDH/1810/Mach/2017-119
Due on : 04.10.2017
Dated : 20.09.2017
At : 02:00 p.m.
- 4.0 The tender should be valid for acceptance for a period of 90 days from the date of tender opening (due date). It is understood that the tenderers are being permitted to tender in consideration of the stipulation on their part that after submitting their tenders they will not resale from their offer(s) or modify the terms and conditions thereof.
- 5.0 If the equipment tendered deviates from tender specifications, a deviation statement should be enclosed with the tender. If there is no deviation "Nil Deviation" confirmation should be enclosed with the tender.
- 6.0 a) If you are a firm (i.e. if you have a Partner or partner(s), the authorized partner holding the Power of Attorney must sign each page of tender. A copy of the partnership agreement should be enclosed. A copy of the Power of Attorney duly executed in his favour authorizing him to bind the firm in all matters pertaining to the contract, including the submission of any dispute relating to business of the firm to arbitration, should be attached to the tender. Original documents are to be shown if and/or when required.

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



LUDHIANA

केन्द्रीय टूल रूम

b) If you are not a firm, the following certificate is to be attached to the tender:

“I certify that I am the sole proprietor and there are no other partner doing business jointly with me.”

c) In case of the limited company, tender documents should be signed by the managing director and the following certificate should be attached to the tender:

“I certify that I am the managing director and I hold the power of attorney executed in accordance with the Articles of Association of the Company to sign all the documents on behalf of the company.”

d) THE REQUISITE CERTIFICATE AS PER (a), (b) OR (c) ABOVE, CURRENT INCOME TAX CLEARANCE CERETIFICATE AND CERTIFICATE OF REGISTRATION WITH DGS&D OR NSIC, IF APPLICABLE, ARE TO BE ENCLOSED WITH PART “A” OF THE TENDER.

7.0 The Tool Room reserves the right to reject any or all offers without assigning any reason whatsoever. The Tool Room also reserves the right to accept any tender in whole or in part without assigning any reason whatsoever. The successful tenderer shall be notified of the acceptance of the tender and till such intimation is received, tenderer(s) should not make any arrangement or incur any expenditure in anticipation of the receipt of notice of acceptance of the tender.

8.0 Machine/equipments/good/software are to be installed and used at Central Tool Room, Ludhiana, Punjab.

Other conditions of the Tender are:

- i) The basic consideration and the essence of the contract shall be strict adherence to the stipulated time schedule for the supply of contracted machine/equipment/goods/software i.e. “Time is the Essence of Contract”.
- ii) Failure and Termination: On acceptance of tender, if the tenderer whose tender is accepted fails to deliver the machine/equipment/goods/software within the period fixed for such delivery in the contract or as extended, or if the contractor repudiates the contract at any time before the expiry of such period, the purchaser may, without prejudice to their other rights-
 - a) Recover from the Contractor Liquidated Damages and by way of penalty a sum equivalent to 2% of the price of any machines /equipments/goods/software (including element of taxes, duties, freights, etc) which the Contractor have failed to deliver within the period fixed for delivery in the contract or as extended, for each month or part of a month for which the delivery of such machine/equipment/goods/software may be in arrears when deliver thereof is accepted after expiry of the aforesaid period subject to maximum of 10.0% of the contract value.

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सूक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

OR

- b) Cancel the contract or a portion thereof and, if so desired and purchase the machine/equipment/goods/software not so delivered or others of a similar description (where machine/equipment/goods exactly complying with particulars are not, in the opinion of the Purchaser [which shall be final] readily procurable) at the risk and cost of the Contractor. It shall, however, be the discretion of the Purchaser to obtain or not, the Performance Guarantee Bond from the firm/firms on whom the contract is placed at the risk and expense of the defaulting firm/firms.
- iii) Force Majeure: The Contractor shall not be liable to forfeiture of security deposit, liquidated damages or termination for default, if and to the extent the delay in performance or other failures to perform its obligations under the contract is the result of an event of Force Majeure. For the purpose of this clause "Force Majeure" means an event beyond the control of the Contractor and not involving the Contractor's fault or negligence and not foreseeable. Such events may include, but are not restricted to, acts of the Purchaser either in its sovereign or contractual capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions and freight embargoes. If a Force Majeure situation arises, the Contractor shall promptly notify the Purchaser in writing of such condition and the cause thereof. Unless otherwise directed by the Purchaser in writing, the Contractor shall continue to perform its obligations under the contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event.
- iv) Any dispute or difference arising in interpretations or applications of provisions of the Contract shall be referred to the sole arbitration of Development Commissioner, Ministry of MSME, Govt. of India or any other person appointed by him. The award of the arbitrator shall be final and binding on both the parties. Arbitration shall be governed by Indian Arbitration Act. In case of any litigation the jurisdiction shall be Ludhiana
- v) In case of any change in the constitution of firm tenderer/contractor shall notify the same to the Tool Room provided that such change shall not relieve any former member/partner of the firm from any liability under the contract and provided that no new member/partner shall be accepted by the firm unless he agrees to abide by all the terms and conditions of this contract.
- vi) These tender documents are non-transferable.

For GENERAL MANAGER

Dated, Ludhiana, 20th September, 2017

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

PART – II(a)

TENDER

To

The General Manager,
Central Tool Room,
A-5, Focal Point,
Ludhiana-141010. (India)

Dear Sir,

I/We agree, on acceptance of the tender in whole or in part, to supply to Central Tool Room, Ludhiana, India, the machine/equipment/goods and accessories, detailed in the Tender enclosed herewith at prices quoted by me/us therein. I/We agree to hold the offer open for 90 days from the due date. I/We have read and understood the terms and conditions of the Tender Documents which shall become Contract on acceptance of tender, and agree to be governed by the same. I/We specifically undertake that I/We will not resile from my/our offer or modify the terms and conditions thereof.

Signature of the Tenderer

Place : _____

Date : _____

Name : _____

Designation : _____

Name & Address : _____

Of the firm _____

WITNESS

Signature : _____

Name : _____

Designation : _____

Name & Address : _____

Of the firm. _____

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

Part-II (b)

Tender

Performa for commercial bid :-

(Tenderer need not use this document exclusively but the offer should be in this format to the extent possible)

1. Tender No. & Date
2. Particulars of item/machine offered:-

<u>Sr. No.</u>	<u>Particulars</u>	<u>Qty.</u>	<u>Rate</u>	<u>Amount</u>
----------------	--------------------	-------------	-------------	---------------

Total _____

3. Particulars of Standard and Essential Accessories and Spares:-

<u>Sr. No.</u>	<u>Particulars</u>	<u>Qty.</u>	<u>Rate</u>	<u>Amount</u>
----------------	--------------------	-------------	-------------	---------------

Total _____

4. Particulars of optional Accessories & Spares:-

<u>Sr. No.</u>	<u>Particulars</u>	<u>Qty.</u>	<u>Rate</u>	<u>Amount</u>
----------------	--------------------	-------------	-------------	---------------

Total _____

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

5. Total Offer Price of Main items and Essential Accessories (2+3): -

<u>Amount</u>	<u>Rate</u>
i) Basic Amount	:
ii) Packing charges	:
iii) Excise duty	:
iv) Sales Tax	:
(We can issue form 'C' and are covered under VAT)	:
v) Forwarding charges	:
vi) Freight (pl. mention mode of Transport also)	:
vii) Transit Insurance	:
viii) Installation charges	:
ix) Commissioning charges	:
x) Training charges (Pl. specify free training and paid training for no. of personnel and days separately)	:
xi) Any other charges (Pl. specify)	:

(CTR will be at liberty to load the bidders & overheads etc. in case these are not indicated explicitly)

Total _____

- xii) Delivery period
xiii) Warranty/Guarantee: -

(Pl. specify the details of parts not covered and mention whether the warranty is for replacement or for repair. Responsibility for transportation etc. for replacement/repair should also be clearly mentioned)

- xiv) Inspection Details: -
xv) Payment terms: -

(Our payment terms are within 30 days after successfully installation of machine. Deviations can be accepted in certain cases. But parties accepting our payment terms shall be preferred)

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

PART – III

TECHNICAL SPECIFICATIONS

1. BASIC HYDRAULIC TRAINING KIT – 02 Set

The Hydraulic Training kit shall be capable to demonstrate the following:

- Basic design and function of a Hydraulic System and valves.
- Basic Circuit Diagrams on practical applications, Hydraulic controls with pilot operated valves, Hydraulic reservoirs, flow distributors etc.
- All Hydraulic connections should be with self-closing, quick connector, safety clamping and quick plug in locking system for profile panels (unless specified against individual item). The couplings should be leak proof, which is self-sealing when decoupled and when coupled, should ensure a tight hydraulic connection. During the coupling process only the face of the coupling should be coated with oil.
- Industrial components should be used in the kit so that the students get hands on practical training in using Industrial components.
- The kit should be modular and upgradable so that future investments to higher levels of training are reduced.
- The operating pressures in general shall be as given below unless otherwise specified against individual item:

Operation Pressure P: 6 MPa (60 Bar)

Max. Permissible pressure Pmax: 12 Mpa (120 Bar)

Each set should consist of:

S. No.	Items	Req. Qty.	Descriptions
1.	Profile plate	01 No.	All of the components should fit securely and safely onto the profile plate. Both sides should have grooves and, if required, both sides can be used. The grooves must be compatible with the ITEM profile system including Side caps. Grid dimensions: 50 mm. ; Size: 1100 x 700 mm.
2.	Pressure gauge	02 Nos.	This gauge should have Effective range and maximum permissible pressure 10 MPa (100 bar) Quality class 1.6% of the full scale value Operating pressure, static: 3/4 of full scale value Operating pressure, dynamic: 2/3 of full scale value Cushioning: Glycerin Low-leakage, self-sealing couplings
3	One-way flow control valve	01 No.	The valve should be used to influence the volumetric flow rate through an adjustable throttle point, in one direction. In the opposite direction, the throttle is bypassed using the non-return valve. <ul style="list-style-type: none">• Actuation: manual• Integrated non-return valve• Operating pressure: 6 MPa (60 bar)• Maximum permissible pressure: 12 MPa (120 bar)• Low-leakage, self-sealing coupling nipples/quick coupling socket

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

4	Shut-off valve	01 No.	The valve should be closed by turning the lever. <ul style="list-style-type: none">• Actuation: manual• Operating pressure: 6 MPa (60 bar)• Maximum permissible pressure: 12 MPa (120 bar)• Low-leakage, self-sealing coupling nipples/quick coupling socket
5	Pressure gauge	02 Nos.	Bourdon tube pressure gauge Display range: 0 – 16 bar
6	Non-return valve 0.1 MPA	01 No.	Operating pressure p: 6 MPa (60 bar) Max. permissible pressure pmax: 12 MPa (120 bar) Actuation: Hydraulic
7	T- Distributor.	05 Nos.	Ports: 2x coupling nipples and 1x quick coupling socket Maximum permissible pressure: 12 MPa (120 bar) Low-leakage, self-sealing couplings
8	Pressure relief valve	02 Nos.	Adjustment: manual, Includes non-return valve, Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar), Low-leakage, self-sealing coupling nipples
9	2-way flow control valve	01 No.	Operating pressure p: 6 MPa (60 bar) Max. permissible pressure pmax: 12 MPa (120 bar) Adjustment: Manual Actuation: Hydraulic
10	Non-return valve-Delockable piloted	01 No.	Surface ratio of pilot piston to non-return valve seat: 3.3 : 1 Operating pressure p: 6 MPa (60 bar) Max. permissible pressure pmax: 12 MPa (120 bar)
11	Double acting cylinder 16/10/200	01 No.	Piston Ø: 16 mm Piston rod Ø: 10 mm, Stroke: 200 mm Surface area ratio- 1 : 1.6 Operating pressure 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar) Double-acting. Low-leakage, self-sealing coupling nipples.
12	4/2 way hand lever valve spring return	01 No.	Actuation: manual Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar).
13	4/3 way hand lever valve by-pass mid position valve	01 No.	Actuation: manual Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar)
14	Hydraulic power pack with constant displacement pump, 230 V	01 No.	Pump design: external gear motor with pressure relief valve adjustable from 0 – 6 MPa (0 – 60 bar), operating pressure 6 MPa (60 bar). Motor: AC, single-phase with overload protection, start capacitor and ON/OFF switch, Tank: 5 l volume, sight glass, temperature display, drain screw Air filter and return filter, low-leakage, self-sealing coupling nipples for P and T Plug socket for unpressurised return Connecting flange for measuring container return Dimensions: 580 x 300 x 180 mm (W x D x H) Weight: 19 kg, Nominal voltage: 230 V AC, Rated output: 0.65 kW, Frequency: 50 to 60 Hz, Delivery rate (rated speed): 2.2 – 2.7 l/min at 1320 – 1680 RPM
15	Quick coupling hose, 600 mm.	08 Nos.	Operating pressure: 6 MPa (60 bar) Max. permissible pressure: 12 MPa (120 bar), Temperature range: -40 – + 125 °C Min. bending radius: 100 mm DN 06 (Ø 6.3 mm)

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सूक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

16	Quick coupling hose,1000 mm.	04 Nos.	Operating pressure: 6 MPa (60 bar) Max. permissible pressure: 12 MPa (120 bar) Temperature range: -40 – + 125 °C Min. bending radius: 100 mm DN 06 (Ø 6,3 mm)
17	Quick coupling hose,1500 mm.	02 Nos.	Operating pressure: 6 MPa (60 bar) Max. permissible pressure: 12 MPa (120 bar) Temperature range: -40 – + 125 °C Min. bending radius 100 mm DN 06 (Ø 6,3 mm)
18	Pressure relief unit	01 No.	The pressure relief unit should be attached to the low-leakage, self-sealing coupling nipple so it can be forced open without requiring much power.
19	Hydraulic oil (HLP22) ,10 L	01 No.	This must be DIN 51524 standards and this should be supplied in a 10 liter can.
20	Oil drip tray	01 No.	The drip tray being supplied should be made of steel. Dimensions: 1160 mm x 760 mm
21	Weight	01 No.	The weight should be capable of being used vertically with a double-acting cylinder. All the necessary accessories for using the weight with the cylinder should be supplied. Mass: 9 kg Dimensions (L x W x H) : 150 x 100 x 80 mm
22	Mounting kit for weight	01 No.	When this mounting kit is mounted, the pulling and pushing load of the basic hydraulics package can be release with it. For this purpose, cylinder and weight are mounted on the mounting kit.
23	Hose holder	01 No.	This should be used to hold hydraulic hoses safe and neatly.
24	Profile plate mounting frame	10 Nos.	The mounting frame should be for inclined assembly of the aluminum profile plate.
25	Manuals	01 Set	All reading material, operating manuals, experiments manual required for using the training kit should be supplied along with the consignment
26	Warranty	02 Years	Min 2 years of warranty should be provided by the supplier.

II. ELECTRO HYDRAULIC TRAINING KIT – 01 Set

The kit should be capable of being used to demonstrate the following:

- Basic design and function of an Electro Hydraulic system.
- Function and identification of Electro Hydraulic components and their symbols Logic AND / OR function to start signals.
- Application and fault findings of Electro Hydraulic controls functional diagrams.
- Systematic design of Electro Hydraulic Sequence Controls.
- Methods for the drafting of circuit diagrams for Electro Hydraulic controls Hydraulic Power Section – Electric Control Section.

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सूक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

Each Electro Hydraulic training kit must have the following items.

S. No.	Items	Req. Qty.	Descriptions
1	Relay, three fold	1 No.	This system consisting of 4 changeover switches, electricity supply rail, mass flow rail, ports for 4 mm safety plugs. The device has three relays with terminals and two buses for power supply. Contact load: max. 5 A, Cut-off load: max. 90 W, Pick-up time: 10 ms. Drop-off time: 8 ms
2	Signal Input, electrical	1 No.	Consisting of: 3 illuminated push buttons, 1 illuminated pressure switch, each with a mini bulb, bus bar, mass flow rail, 1 NO contacts and 1 NC contacts for 4 mm security plugs. The device contains an illuminated Pushbutton switch (control switch) and three illuminated pushbuttons (momentary contact switches) with terminals and two buses for power supply. Contact set: 1 makes, 1 breaks, Contact load: Maximum 2 A Power consumption (Miniature bulb): 0.48 W
3	Limit switch, electrical left-actuated	1 No.	The micro switch is actuated mechanically when the roller lever is pressed, for example by the trip cam of a cylinder. The micro switch can be wired as N/O contact, N/C contact or a changeover switch, using the 4 mm safety sockets integrated in the quick action mounting system. Possible contact load: maximum 5 A.
4	Limit switch, electrical right-actuated	01 No.	The micro switch is actuated mechanically when the roller lever is pressed, for example by the trip cam of a cylinder. The micro switch can be wired as a N/O contact, N/C contact or a changeover switch, using the 4 mm safety sockets integrated in the quick action mounting system. Possible contact load: maximum 5 A
5	4/2-way single solenoid valve, spring return	01 No.	Actuation: switching solenoid Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar) 24 V DC, power: 6.5 W output Electrical connection: 4 mm safety socket
6	4/3-way solenoid valve, closed mid-position	01 No.	Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar) Valve port pattern, 24 V DC, power: 6.5 W output Electrical connection: 4 mm safety socket
7	Mounting kit for cylinders	01 No.	Actuation of the stem actuated valve by the guide bar Actuation of proximity sensors by the permanent magnet of the guide bar Use of a displacement encoder
8	Pressure switch, electronic	01 No.	Operating voltage: 18 – 35 V DC Switching outputs: 2 x PNP, maximum 1.2 A Effective range and maximum permissible pressure: 10 MPa (100 bar) Analogue output: 0 – 10 V 4-digit digital display, can be rotated along 2 axes
9	Proximity switch, electronic	02 Nos.	Contactless proximity sensor for mounting on drives with T-slot, with connecting cable and LED operating status indicator. Protected against polarity reversal, overload and short circuit. Power supply: 10 – 30 V DC Switching output, N/O contact (PNP): maximum 200 mA Electrical connection M8, 3-pin on 4 mm safety plug
10	Power supply unit	01 No.	Input voltage: 85 – 265 V AC (47 – 63 Hz) Output voltage: 24 V DC, short-circuit-proof Output current: max. 4.5 A Dimensions: 170 x 240 x 92 mm

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

11	Set of cables	01 Set	Complete set, consisting of 98 safety laboratory cables with 4 mm safety plugs in the colours red and blue: 10 x red 50 mm 10 x blue 50 mm 26 x red 300 mm 11 x blue 300 mm 21 x red 500 mm 12 x blue 500 mm 03 x red 1000 mm 03 x blue 1000 mm 01 x red 1500 mm 01 x blue 1500 mm
12	Manuals	01 Set	All reading material, operating manuals, experiments manual required for using the training kit should be supplied along with the consignment
13	Warranty	02 Years	Min 2 years of warranty should be provided by the supplier.

III: MEASUREMENT AND CONTROL IN HYDRAULICS:-

Each training kit must have the following items.

S. No.	Items	Req. Qty.	Descriptions
1	I/O data cable, 2.5 m	01 No.	For connection of interfaces, for example an interface unit, with the universal connection unit, digital.
2	Universal connection unit, digital	01 No.	The universal connection unit should connect all 4 mm safety plugs with the 24-pin system connector as per IEEE 488. It thus becomes a universal interface between units with 4 mm connection technology and devices equipped with connectors as per IEEE488: Inputs: 3 safety sockets each for 8 three-wire sensors Outputs: 2 safety sockets each for 8 actuators Connections: 4 mm safety sockets for 24 V DC, connector (IEEE488) I/O status display: Via LED
3	Connection unit, analogue	01 No.	For ER-unit cabinet frame for the connection of 4 mm security sockets to an analogue cable. Permissible voltage range: 22 – 27 V DC, Reference Ground Analogue voltage input: Input U 4, Range: -10 – +10 V, (max. 30 V), Input resistance: 200 k Ω , Analogue voltage input I 4, Range: 0 – 20 mA, Input resistance: max. \pm 30 V, Analogue output: 2, Voltage: -10 – +10 V, Short circuit proof: max. \pm 30 V, protected, current: max. 20 mA
4	Analogue cable	01 No.	Analogue cable, parallel, 15-pin SUB-D type connector on both ends, 150 cm
5	Interface unit	01 No.	2 x 24 pin IEEE 488 compatible plug connectors for mechatronics station, training package, PLCs each with 8 digital inputs and 8 digital outputs (16I /16O) 1 x SUB D 15-pin plug connector for mechatronic station, training package, PLC with 4 analogue inputs and 2 analogue outputs (12 bit resolution) 24 V power supply connection via separate screw terminals USB 2.0 interface to PC (galvanically separated) Large LCD display Display of digital signals via LED

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises

Government of India

केन्द्रीय टूल रूम

सूक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.

भारत सरकार



केन्द्रीय टूल रूम

6	4/3 way solenoid valve, relieving mid-position	01 No.	Actuation: switching solenoid Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar) 24 V DC, power: 6.5 W output Electrical connection: 4 mm safety socket Quick action mounting system.
7	Pressure sensor	02 Nos.	Operating voltage: 15 – 30 V DC Effective range and maximum permissible pressure: 10 MPa (100 bar) Analogue output: 0 – 10 V Electrical connection: on 4 mm safety plug Low-leakage, self-sealing couplings
8	Flow control valve	01 No.	Actuation: manual Operating pressure: 6 MPa (60 bar) Maximum permissible pressure: 12 MPa (120 bar) Low-leakage, self-sealing coupling nipples/quick coupling socket
9	Quick hose line with QRC, 1000 mm	01 No.	Operating pressure: 6 MPa (60 bar) Max. permissible pressure: 12 MPa (120 bar) Temperature range: -40 – +125 °C Min. bending radius: 100 mm DN 04 (Ø 4 mm)
10	Software for Measurement & Control in hydraulic	01 User	Software for acquisition, display and documentation of analogue measured values in hydraulic equipment and systems through the use of common industrial sensors with voltage output signal for pressure, force and flow rate with exercises and didactic assistance. Results should be gauged with measuring points, printed out or exported to a spread sheet programme. Furthermore, the software also should include the entire collection of exercises as a PDF file.
11	Electrical Limit switch (actuation from left side)	01 No.	The micro switch is actuated mechanically when the roller lever is pressed, for example by the trip cam of a cylinder. The micro switch can be wired as an N/O contact, N/C contact or a changeover switch, using the 4 mm safety sockets integrated in the quick action mounting system. Possible contact load: maximum 5 A
12	WorkStation with 1 drawer unit (for Hydraulic)	01 Unit	Dimension of table (L x W x H): 1200 x 900 x 900 mm. (min.) with four castor wheel and two lockable at front side. One drawer unit for storing Hydraulic components.
13	Manuals	01 Set	All reading material, operating manuals, experiments manual required for using the training kit should be supplied along with the consignment
14	Warranty	02 Years	Min 2 years of warranty should be provided by the supplier.

Notes:

1. Certification training from OEM of min. 7 days (phase-wise) to be provided on FOC basis in CTR.
2. Authorization certificate from OEM to be provided.
3. The supplier shall be required to submit a performance bank guarantee of value equal to 10% of the order value, for the warranty period.

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com



CENTRAL TOOL ROOM, LUDHIANA

Ministry of Micro Small & Medium Enterprises
Government of India

केन्द्रीय टूल रूम

सुक्ष्म, लघु एवं मध्यम उद्योग मंत्रालय.
भारत सरकार



PART – IV

SPECIAL CONDITIONS:

1. Training of Purchaser's staff is tenderer's responsibility.
2. Delivery Schedule: As per the terms of purchase order.
3. The tender is required to give on a separate sheet for Total Life Cycle costing of the supply.
4. Position of availability of Service Engineer in case of break down / support, along with expected time to reach CTR and position of availability of spare parts in future should clearly be stated.

Signature of the Tenderer

Place: _____

Name :

Date: _____

Designation :

Name & Address of the firm : _____

WITNESS

Signature :

Name :

Designation :

Name & Address of the firm :

A-5, Focal Point, Ludhiana - 141010

Tel: (+91)-0161- 2670059 (Ext. 237), 2670058, 2676166, 2673564

Fax: (+91)-0161-2674746.

E-mail: info@ctrludhiana.com ; purchase@ctrludhiana.com ; Visit us at : www.ctrludhiana.com